

Recessed mechanical shower mixer

Ref. 254BOX-2541

Recessed mechanical shower mixer in a waterproof housing



DESCRIPTION

Recessed mechanical shower mixer - Ref.254BOX-2541

Mechanical shower mixer which can be recessed.

- Single control mixer with Ø 40mm ceramic cartridge.

Pre-set maximum temperature limiter

Thermal shocks are easy to undertake without removing the control lever or shutting off the cold water.

Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head.

Solid control lever.

Order a wall-mounted outlet or shower head to complete.

Bright polished stainless steel cover plate 166 x 166mm.

- Waterproof recessing housing:

- Collar with waterproof seal.
- Hydraulic connection from the outside and maintenance from the front.
- Adjusts to all types of installations (rails, solid walls, panels).
- Compatible with wall finishes 10 - 120mm (while maintaining the minimum recessing depth of 93mm).
- Suitable for standard or "pipe in pipe" supply.
- Stopcocks and flow rate adjustment, filters, non-return valves and cartridge are all integrated and accessible from the front.
- Supplied in 2 kits: secure system flush without sensitive elements.

- Shower mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Suitable for people with reduced mobility.

10-year warranty.

Kit composition:

(254BOX): recessing housing with protection, valve configured for system purge, connection accessories.

(2541): control plate, valve, waterproof seal, interior reinforcement part.

ADVANTAGES

TECHNICAL CHARACTERISTICS

Recessed mechanical shower mixer - Ref.254BOX-2541

| | |
|-----------|---|
| Flow rate | Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head |
| Connector | 1/2" |
| Finish | Chrome-plated brass |

