

SECURITHERM shower panel

Ref. H9634

Sequential thermostatic

DESCRIPTION

SECURITHERM shower panel - Ref.H9634

Anodised aluminium shower panel for wall-mounted exposed installation: SECURITHERM sequential thermostatic mixer (non time flow).

Adjustable temperature control from cold water up to 39°C; maximum temperature limiter set at 39°C, can be adjusted.

Anti-scalding safety: automatic shut-off if cold water supply fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Thermal shocks are possible.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.

Hygiene control lever L. 100mm.

Concealed supply via M1/2" flexibles.

Concealed fixings.

Filters.

Suitable for people with reduced mobility.

10-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref.H9634

Technology	Sequential thermostatic SECURITHERM
Height	1050 mm
Flow rate	6 lpm
Connector	M1/2"
Finish	Aluminium
Supply	Concealed, via M1/2" flexible
Temperature limiter	39 °C
Width	210 mm
Water supply	Concealed



ADVANTAGES



SECURITHERM: Optimum anti-scalding safety



Maximum hygiene: no non-return valves



Thermostatic: total temperature stability



Sequential: open and closing on cold water

