

BINOPTIC electronic tap

Ref. 37801515

Mains supply, Ø 15mm conical inlet

DESCRIPTION

BINOPTIC electronic tap - Ref.37801515

Deck-mounted electronic basin tap:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24hr after last use).
Active, infrared movement detection, sensor at the end of the spout optimises detection.
Chrome-plated solid brass body.
PEX flexible with filter, solenoid valve and Ø 15mm conical inlet.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with a smooth interior and low volume of water (limits bacterial niches).
Suitable for people with reduced mobility.
10-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref.37801515

Technology	Electronic
Flow rate	3 lpm
Connector	M1/2" Ø 15mm
Supply	230/12V mains supply
Drop Height	90 mm
Spout Length	125 mm
Installation:	Deck-mounted



ADVANTAGES



Total hygiene: no manual contact



90% water savings



Independent IP65 electronic control unit



Anti-bacterial proliferation duty flush

