
DELABIE

PREMIX SECURITY

Ref. 731053

Group thermostatic mixing valve for circulating loops 44°-58°C



DESCRIPTION

PREMIX SECURITY - Ref.731053

Group thermostatic mixing valve for hot water circulating loops adjustable from 44°C to 58°C:
Anti-scalding safety.
Regulates temperature variations.
Non-return valves and filters accessible from the exterior without having to remove the mechanism.
Thermal cartridge with no specific lever needed (push-button on the control knob).
Interchangeable cartridge with thermostatic cell.
High-resistance chrome-plated brass body.
Maximum hot water temperature: 85°C.
Differential hot water / mixed water: 15°C mini.
Pressure differences at the entrance: 1 bar maximum (0.5 bar recommended).
Minimum pressure / maximum: 1 to 10 bar (1 to 5 bar recommended).
Left hand side hot water inlet (red ring) and right hand side cold water inlet (blue ring).
Mixed water outlet at the top (purple ring) for bottom outlet: unscrew / place lid at the top and outlet connector at the bottom.
15% energy savings: optimised heat loss (comparison between a circulating loop at 55°C and a non-circulating system at 70°C).
Safety and prolongation of system life span (Hot water > 65°C leads to premature aging within the system).
Maximum temperature limiter, can be adjusted by the installer.
Reduced risk of scalding by limiting temperature at the point-of-use.
90 lpm - M1".
10-year warranty.


ADVANTAGES

© Delabie

TECHNICAL CHARACTERISTICS

PREMIX SECURITY - Ref.731053

Technology	Thermostatic
Height	80 mm
Length	160 mm
Flow rate	90 lpm
Connector	M1"
Depth	23 mm



© Delabie