

PREMIX COMFORT

Ref. 731004

Group thermostatic mixing valve, mixed water 32°-42°C



DESCRIPTION

PREMIX COMFORT - Ref.731004

Group thermostatic mixing valve for mixed water from 32° to 42°C:

Anti-scalding safety.

Regulation of temperature variations.

Non-return valves and filters accessible from the exterior without having to remove the mechanism.

Thermal cartridge with no specific lever needed (push-button on the control knob).

Interchangeable cartridge with automotive cell.

High-resistance chrome-plated brass body.

Maximum hot water temperature: 85°C.

Differential hot water / mixed water: 15°C mini.

Pressure differences at the entrance: 1 bar maximum (0.5 bar recommended).

Minimum pressure / maximum: 1 to 10 bar (1 to 5 bar recommended).

Left hand side hot water inlet (red ring) and right hand side cold water inlet (blue ring).

Mixed water outlet at the top (purple ring).

For bottom outlet: unscrew / place lid at the top and outlet connector at the bottom.

Maximum temperature limiter, can be adjusted by the installer.

Reduced risk of scalding by limiting temperature at the point-of-use.

140 lpm - M1 1/4".

10-year warranty.

ADVANTAGES



Automatic shut-off if cold water fails Temperature stability



Accessible filters and non-return valves



Automotive thermo-reactive cell

TECHNICAL CHARACTERISTICS

PREMIX COMFORT - Ref.731004

Technology	Thermostatic
Height	90 mm
Length	180 mm
Flow rate	140 lpm
Connector	M1"1/4
Depth	26 mm

