

## TEMPOFIX 3 self-supporting frame system with time flow WC valve

Ref. 578405-578222

3L/6L dual flush time flow valve



### DESCRIPTION

#### TEMPOFIX 3 self-supporting frame system with time flow WC valve -

Ref.578405-578222

Self-supporting frame system for wall-hung WCs: - Black powder-coated steel frame. - Fixes to load-bearing floors. - Frame height can be adjusted from 0 - 200mm (with 1m mark). - Ø 32mm flush tube with Ø 55mm connection washer. - Ø 100mm soil pipe and PVC collar with waterproof seal, with 2 settings positions. - Delivered pre-mounted. - For semi-thick walls 30 - 60mm. - 10-year warranty. Fitted with TEMPOFLUX 2 direct flush time flow valve: - Ø 195mm chrome-plated wall plate with concealed fixings. - 3L/6L dual flush (can be adjusted to 2L/4L). - Soft-touch operation. - Vacuum breaker. - Stopcock and flow rate/volume adjuster. - Solid brass body and shock-resistant, scale-resistant mechanism. - In-line inlet M3/4". - Acoustic level complies with European standard EN 12541 class II.

Technical features: see TEMPOFLUX 2 ref. 762902. Kit contents: (578405): self-supporting WC, soil pipe Ø 100mm, flush tube, valve with cover, vacuum breaker, connection accessories. (578222): control plate, fixings.

ADVANTAGES Maintenance aisée - Installation aisée Easy and quick to install: supplied pre-mounted Anti-vandalisme Self-supporting frame system Economie d'eau 3L/6L dual flush, can be adjusted to 2L/4L Hygiène - Anti-bactérien - BIOSAFE Direct flush: no water stagnation Self-supporting frame system for wall-hung WCs: - Black powder-coated steel frame. - Fixes to load-bearing floors. - Frame height can be adjusted from 0 - 200mm (with 1m mark). - Ø 32mm flush tube with Ø 55mm connection washer. - Ø 100mm soil pipe and PVC collar with waterproof seal, with 2 settings positions. - Delivered pre-mounted. - For semi-thick walls 30 - 60mm. - 10-year warranty. Fitted with TEMPOFLUX 2 direct flush time flow valve: - Ø 195mm chrome-plated wall plate with concealed fixings. - 3L/6L dual flush (can be adjusted to 2L/4L). - Soft-touch operation. - Vacuum breaker. - Stopcock and flow rate/volume adjuster. - Solid brass body and shock-resistant, scale-resistant mechanism. - In-line inlet M3/4". - Acoustic level complies with European standard EN 12541 class II. Technical features: see TEMPOFLUX 2 ref. 762902. Kit contents: (578405): self-supporting WC, soil pipe Ø 100mm, flush tube, valve with cover, vacuum breaker, connection accessories. (578222): control plate, fixings.

ADVANTAGES Maintenance aisée - Installation aisée Easy and quick to install: supplied pre-mounted Anti-vandalisme Self-supporting frame system Economie d'eau 3L/6L dual flush, can be adjusted to 2L/4L Hygiène - Anti-bactérien - BIOSAFE Direct flush: no water stagnation Self-supporting frame system for wall-hung WCs: - Black powder-coated steel frame. - Fixes to load-bearing floors. - Frame height can be adjusted from 0 - 200mm (with 1m mark). - Ø 32mm flush tube with Ø 55mm connection washer. - Ø 100mm soil pipe and PVC collar with waterproof seal, with 2 settings positions. - Delivered pre-mounted. - For semi-thick walls 30 - 60mm. - 10-year warranty. Fitted with TEMPOFLUX 2 direct flush time flow valve: - Ø 195mm chrome-plated wall plate with concealed fixings. - 3L/6L

### ADVANTAGES



Easy and quick to install: supplied pre-mounted



Self-supporting frame system



3L/6L dual flush, can be adjusted to 2L/4L



Direct flush: no water stagnation

level complies with European standard EN 12541 class II. Technical features: see TEMPOFLUX 2 ref. 762902. Kit contents: (578405): self-supporting WC, soil pipe Ø 100mm, flush tube, valve with cover, vacuum breaker, connection accessories. (578222): control plate, fixings.

## TECHNICAL CHARACTERISTICS

### TEMPOFIX 3 self-supporting frame system with time flow WC valve -

[Ref.578405-578222](#)

|            |                     |
|------------|---------------------|
| Technology | Time flow           |
| Height     | 1000 - 1320 mm      |
| Connector  | 3/4"                |
| Finish     | Chrome-plated metal |
| Width      | 350 mm              |
| Depth      | 157 - 177 mm        |