

## TEMPOFIX 3 self-supporting frame system with time flow WC valve

Ref. 578305-578230

3L/6L dual flush time flow valve

### DESCRIPTION

#### TEMPOFIX 3 self-supporting frame system with time flow WC valve -

**Ref.578305-578230**

Self-supporting frame system for wall-hung WCs:

- Black powder-coated steel frame.
- Fixes to load-bearing floors.
- Frame height can be adjusted from 0 to 200mm (with 1m mark).
- Ø 32mm flush tube with Ø 55mm connection washer.
- Ø 100mm soil pipe and PVC collar with waterproof seal, with 2 settings positions.
- Delivered pre-mounted.
- For thick walls 70 - 130mm.
- 10-year warranty.

Fitted with TEMPOFLUX 2 direct flush time flow valve:

- Ø 195mm chrome-plated wall plate with concealed fixings.
- 3L/6L dual flush can be adjusted to 2L/4L.
- Soft-touch operation.
- Vacuum breaker.
- Stopcock and flow rate/volume adjuster.
- Solid brass body and shock-resistant, scale-resistant mechanism.
- In-line inlet M $\frac{3}{4}$ ".
- Acoustic level complies with European standard EN 12541 class II.

Technical features: see TEMPOFLUX 2 ref. 762902.

Kit contents:

(578305): frame system, soil pipe Ø 100mm, flush tube, valve with cover, vacuum breaker, connection accessories.

(578230): control plate, fixings.



### ADVANTAGES



Easy and quick to install:  
supplied pre-mounted



Self-supporting frame system



3L/6L dual flush, can be  
adjusted to 2L/4L



Direct flush: no water  
stagnation

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 self-supporting frame system with time flow WC valve -

Ref.578305-578230

|            |                     |
|------------|---------------------|
| Technology | Time flow           |
| Height     | 1000 - 1320 mm      |
| Connector  | 3/4"                |
| Finish     | Chrome-plated metal |
| Width      | 350 mm              |
| Depth      | 157 - 177 mm        |

