

TEMPOFIX 3 self-supporting frame system for WCs

Ref. 578405BE-578212

6L single flush time flow valve - Ø 90mm soil pipe

DESCRIPTION

TEMPOFIX 3 self-supporting frame system for WCs -

[Ref.578405BE-578212](#)

Self-supporting frame system W. 350mm for wall-hung WCs: - Black powder-coated steel frame. - Fixes to load-bearing floors. - Frame height can be adjusted from 0 - 200mm (with 1m mark). - Ø 32mm flush tube with Ø 55mm connection washer. - Ø 90mm HDPE soil pipe with waterproof seal, with 2 settings positions. - Delivered pre-mounted. - For semi-thick walls 30 - 60mm. - 10-year warranty. Fitted with TEMPOFLUX 2 direct flush time flow valve: - Ø 195mm chrome-plated wall plate with concealed fixings. - 6L single flush. - Soft-touch operation. - Vacuum breaker. - Stopcock and flow rate/volume adjuster. - Solid brass body and shock-resistant, scale-resistant mechanism. - In-line inlet M3/4". - Acoustic level complies with European standard EN class II. Technical characteristics: see TEMPOFLUX 2 ref. 762901. Kit contents: (578405BE): self-supporting WC, soil pipe Ø 90mm, flush tube, valve with cover, vacuum breaker, connection accessories. (578212): control plate, fixings.

TECHNICAL CHARACTERISTICS





TEMPOFIX 3 self-supporting frame system for WCs -

[Ref.578405BE-578212](#)

Technology	Time flow
Height	1000 - 1320 mm
Connector	3/4"
Width	350 mm
Depth	170 - 190 mm



ADVANTAGES

-  Easy and quick to install: supplied pre-mounted
-  Self-supporting frame system
-  Soft-touch operation
-  Direct flush: no water stagnation