DELABIE

TEMPOFIX 3 self-supporting frame system for WCs



Ref. 578305DE-578222

3L/6L dual flush time flow valve - Ø 110mm soil pipe

DESCRIPTION

TEMPOFIX 3 self-supporting frame system for WCs -

Ref.578305DE-578222

Self-supporting frame system W. 350mm for wall-hung WCs: - Black powder-coated steel frame. - Fixes to load-bearing floors. - Frame height can be adjusted from 0 to 200mm (with 1m mark). - Ø 32mm flush tube with Ø 55mm connection washer. - Ø 110mm HDPE soil pipe with waterproof seal, with 2 settings positions. - Delivered pre-mounted. - For dry walls 10 - 35mm. - 10-year warranty. Fitted with TEMPOFLUX 2 time flow direct flush valve: - Ø 195mm chrome-plated wall plate with concealed fixings. - 3L/6L dual flush (can be adjusted to 2L/4L). - Soft-touch operation. - Vacuum breaker. - Stopcock and flow rate/volume adjuster. - Solid brass body and shock-resistant, scale-resistant mechanism. - In-line inlet M3/4". - Acoustic level complies with European standard EN class II. Technical features: see TEMPOFLUX 2 ref. 762902. Kit contents: (578305DE): frame system, soil pipe Ø 110mm, flush tube, valve with cover, vacuum breaker, connection accessories. (578222): control plate, fixings.

ADVANTAGES

- Easy and quick to install: supplied pre-mounted
- Self-supporting frame system
- 3L/6L dual flush, can be adjusted to 2L/4L
- Direct flush: no water stagnation

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 self-supporting frame system for WCs -

Ref.578305DE-578222

Technology	Time flow
Height	1000 - 1320 mm
Connector	3/4"
Finish	Chrome-plated metal
Width	350 mm
Depth	170 - 190 mm

© Delabie