

TEMPOFIX 3 self-supporting frame system for WCs

Ref. 578405DE-578212

6L single flush time flow valve - Ø 110mm soil pipe

DESCRIPTION

TEMPOFIX 3 self-supporting frame system for WCs -

[Ref.578405DE-578212](#)

Self-supporting frame system W. 350mm for wall-hung WCs:

- Black powder-coated steel frame.
- Fixes to load-bearing floors.
- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- Ø 32mm flush tube with Ø 55mm connection washer.
- Ø 110mm HDPE soil pipe with waterproof seal, with 2 settings positions.
- Delivered pre-mounted.
- For semi-thick walls 30 - 60mm.
- 10-year warranty.

Fitted with TEMPOFLUX 2 direct flush time flow valve:

- Ø 195mm chrome-plated metal wall plate with concealed fixings.
- 6L single flush.
- Soft-touch operation.
- Vacuum breaker.
- Stopcock and flow rate/volume adjuster.
- Solid brass body and shock-resistant, scale-resistant mechanism.
- In-line inlet M $\frac{3}{4}$ ".
- Acoustic level complies with European standard EN class II.

Technical features: see TEMPOFLUX 2 ref. 762901.

Kit contents:

(578405DE): self-supporting WC, soil pipe Ø 110mm, flush tube, valve with cover, vacuum breaker, connection accessories.

(578212): control plate, fixings.



ADVANTAGES



Easy and quick to install:
supplied pre-mounted



Self-supporting frame system



Soft-touch operation



Direct flush: no water
stagnation

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 self-supporting frame system for WCs -

Ref.578405DE-578212

Technology	Time flow
Height	1000 - 1320 mm
Connector	3/4"
Finish	Chrome-plated metal
Width	350 mm
Depth	170 - 190 mm

