

TEMPOFIX 3 self-supporting frame system with electronic WC valve

Ref. 564065-464006

TEMPOMATIC battery-operated dual control electronic valve

DESCRIPTION

TEMPOFIX 3 self-supporting frame system with electronic WC valve -

Ref.564065-464006

Frame system for wall-hung WCs:

Black powder-coated steel frame.

Self-supporting frame system for fixing to load-bearing floors.

Frame height can be adjusted from 0 - 200mm (with 1m mark).

Ø 32mm flush tube with Ø 55mm connection washer.

PVC soil pipe, Ø 100mm outlet to be glued onto the waterproof seal, with 2 setting positions.

Delivered pre-mounted.

Compatible with solid walls from 10 - 120mm.

10-year warranty.

Fitted with TEMPOMATIC dual control F¾" electronic direct flush valve:

- Battery-operated with 123 6V Lithium batteries.
- Satin finish stainless steel wall plate 186 x 186mm and chrome-plated metal button with integrated electronics.
- Waterproof recessing housing.
- Detection delay is 10 seconds.
- Voluntary activation (push-button with anti-blocking) or automatically when the user leaves.
- "Intelligent" automatic rinsing (flush volume adapts according to use).
- 3 programmes (rinsing volume can be set according to type of WC pan).
- Hygienic duty flush, every 24 hours (can be adjusted to 12 hours or OFF) after the last use.
- Backflow prevention device inside the housing.
- Integrated stopcock and flow rate adjuster.
- Compatible with sea water and grey water.

Technical characteristics: see TEMPOMATIC dual control ref. 464PBOX-464006.

Kit contents:

(564065): frame system, soil pipe Ø 100mm, flush tube, recessed housing with cover, valve for system flush, vacuum breaker, stopcock, connection accessories.

(464006): control plate, 6V lithium batteries, collar for waterproofing, solenoid valve, cartridge.



ADVANTAGES



Total hygiene: no manual contact



Quick and easy to install: delivered pre-mounted



Direct flush: no stagnant water



Voluntary or automatic flush

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 self-supporting frame system with electronic WC valve -

Ref.564065-464006

Technology	Electronic and time flow
Height	1000 - 1320 mm
Connector	3/4"
Finish	Satin finish stainless steel
Supply	6V batteries
Width	350 mm
Depth	157 - 177 mm

