

TEMPOFIX 3 self-supporting frame system with electronic WC valve

Ref. 547005-546412

Mains supply electronic valve

DESCRIPTION

TEMPOFIX 3 self-supporting frame system with electronic WC valve -

[Ref.547005-546412](#)

Self-supporting frame system for wall-hung WCs: - Black powder-coated steel frame. - Fixes to load-bearing floors. - Frame height can be adjusted from 0 - 200mm (with 1m mark). - Ø 32mm flush tube with Ø 55mm connection washer. - PVC soil pipe, Ø 100mm outlet to be glued to waterproof seal, with 2 setting positions. - Delivered pre-mounted. - Compatible with solid walls from 26 - 130mm. - 10-year warranty. Fitted with TEMPOMATIC F1" electronic direct flush valve: - Mains supply with 1" solenoid valve. - 230/12V transformer. - IP65 independent electronic unit. - Recessing housing below stainless steel wall plate 320 x 220mm. - Shock-resistant infrared presence detection sensor. - Voluntary activation flush (when hand is detected ~4cm in front of the sensor) or automatically (when the user leaves). - Time flow ~7 seconds can be adjusted 3 - 12 seconds. - Detection distance and flow rate/volume can be adjusted by the installer. - Suitable for rimless pans without flow rate regulation and suitable for people with reduced mobility. Technical characteristics: see TEMPOMATIC WC ref. 463326. Kit contents: (547005): frame system, Ø 100mm soil pipe, flush tube, valve, electronic housing, connection accessories. (546412): control plate, fixings.



ADVANTAGES



Total hygiene: no manual contact



Self-supporting frame system



Easy and quick to install: supplied pre-mounted



Direct flush: no water stagnation

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 self-supporting frame system with electronic WC valve -

[Ref.547005-546412](#)

Technology	Electronic
Height	1000 - 1320 mm
Connector	1"
Finish	Satin finish stainless steel
Supply	Mains supply 230/12V
Width	350 mm
Depth	157 - 177 mm