

TEMPOFIX 3 wall-mounted frame system for WCs

Ref. 547000BE-546412

Mains supply electronic valve - Ø 90mm soil pipe



DESCRIPTION

TEMPOFIX 3 wall-mounted frame system for WCs -

Ref.547000BE-546412

Wall-mounted frame system W. 350mm for wall-hung WCs:

- Black powder-coated steel frame.
- Fixes to load-bearing walls.
- Frame height can be adjusted from 0 to 200mm (with 1m mark).
- Ø 32mm flush tube with Ø 55mm connection washer.
- Ø 90mm ABS soil pipe with waterproof seal, with 2 settings positions.
- Delivered pre-mounted.
- For dry walls 26 - 130mm.
- 10-year warranty.

Fitted with TEMPOMATIC F1" electronic direct flush valve:

- Mains supply with 1" solenoid valve.
- Stainless steel plate 320 x 220mm.
- IP65 independent electronic unit.
- 230/12V transformer.
- Shock-resistant infrared presence detection sensor.
- Voluntary activation flush when user's hand approaches the sensor or automatically when the user leaves.
- Time flow ~7 seconds can be adjusted 3 - 12 seconds.
- Stopcock and volume/flow rate adjuster.
- Detection distance can be adjusted by installer.

Technical characteristics: see TEMPOMATIC WC ref. 463326.

Kit contents:

(547000BE): frame system, soil pipe Ø 90mm, flush tube, valve, electronic housing, connection accessories.

(546412): control plate, fixings.

ADVANTAGES



Total hygiene: no manual contact



Install behind the wall



Quick and easy to install: supplied



pre-mounted



Direct flush: no stagnant water

TECHNICAL CHARACTERISTICS

TEMPOFIX 3 wall-mounted frame system for WCs -

Ref.547000BE-546412

Technology	Electronic
Height	1000 - 1320 mm
Connector	1"
Width	350 mm
Depth	170 - 190 mm

