

## TEMPOMATIC direct flush valve

Ref. 463326

Electronic mains supply



### DESCRIPTION

#### TEMPOMATIC direct flush valve - Ref.463326

Flush system without cistern: directly connected to pipework.  
 Mains supply with 1" solenoid valve.  
 230/12V transformer.  
 IP65 independent electronic unit.  
 Housing recessed behind a satin finish stainless steel wall plate 320 x 220mm.  
 Shock-resistant infrared presence detection sensor.  
 Voluntary activation (when hand is detected ~4cm in front of the sensor) or automatic flush when the user leaves.  
 Time flow ~7 seconds, can be adjusted from 3 - 12 seconds.  
 Detection distance, flow rate and flush volume can be adjusted.  
 Stopcock FF1".  
 Vacuum breaker Ø 32mm.  
 Connection washer Ø 32/55mm.  
 Base flow rate: 1 L/sec.  
 Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.  
 10-year warranty.





This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).

### TECHNICAL CHARACTERISTICS

#### TEMPOMATIC direct flush valve - Ref.463326

Technology	Electronic
Height	320 mm
Connector	1"
Finish	Satin finish stainless steel
Supply	230/12V mains supply
Width	220 mm
Depth	100 mm min

### ADVANTAGES

-  Total hygiene: operate without manual contact
-  No cistern: no stagnant water
-  Voluntary or automatic flush
-  Wall recessed installation

