

## TEMPOFLUX 3 direct flush WC valve

Ref. 763BOX-763000

Recessed in a waterproof box. Satin st. steel







### DESCRIPTION

#### TEMPOFLUX 3 direct flush WC valve - Ref.763BOX-763000

TEMPOFLUX 3 recessed time flow direct flush valve: Satin finish stainless steel wall plate 210 x 162mm. Waterproof recessing housing: - Collar with waterproof seal. - Hydraulic connection to the outside and maintenance from the front. - Adjusts to all types of installation (rails, solid walls, panels). - Compatible with wall finishes from 10 - 120mm (while maintaining the minimum recessing depth of 93mm). - Suitable for standard or "pipe-in-pipe" supply. - Stopcock and flow rate adjustment, activation unit and cartridge are all integrated and accessible from the front. - TEMPOFLUX 3 F3/4" flush valve is compatible with sea water and grey water. - Back flow prevention device inside the housing. - Supplied in 2 kits: secure system flush without sensitive elements. Soft-touch operation. AB Anti-blocking system: flush only takes place once the push-button is released. Dual flush 3L/6L can be adjusted to 2L/4L. Outlet connection for PVC tube Ø 26/32mm. Acoustic level complies with European standard EN 12541 (class II acoustic level). Base flow rate: 1 l/sec. Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility. 10-year warranty. Kit contents: (763BOX): recessed housing with cover, valve configured for system flush, vacuum breaker, stopcock, connection accessories. (763000): control plate, collar for waterproofing, time flow cartridge.

### ADVANTAGES

-  Soft-touch operation
-  Direct flush: no standing water
-  Dual flush 3L/6L
-  Waterproof housing, adjustable and modular

## TECHNICAL CHARACTERISTICS

### TEMPOFLUX 3 direct flush WC valve - [Ref.763BOX-763000](#)

Technology	Time flow
Height	210 mm
Connector	F $\frac{3}{4}$ "
Finish	Stainless steel satin finish
Width	162 mm
Depth	93 - 190 mm