# TEMPOFLUX 3 direct flush WC valve

Ref. 763BOX-763040

Time flow dual flush 3L/6L, AB system



### **DESCRIPTION**

#### TEMPOFLUX 3 direct flush WC valve - Ref.763BOX-763040

TEMPOFLUX 3 recessed time flow direct flush valve:

Chrome-plated metal wall plate 170 x 170mm.

Waterproof recessing housing:

- Collar with waterproof seal.
- Hydraulic connection to the outside and maintenance from the front.
- Adjusts to all types of installation (rails, solid walls, panels).
- Compatible with wall finishes from 10 120mm (while maintaining the minimum recessing depth of 93mm).
- Suitable for standard or "pipe-in-pipe" supply.
- Stopcock and flow rate adjustment, activation unit and cartridge are all integrated and accessible from the front.
- TEMPOFLUX 3 F¾" flush valve is compatible with sea water and grey water
- Back flow prevention device inside the housing.
- Supplied in 2 kits: secure system flush without sensitive elements. Soft-touch operation.

AB Anti-blocking system: flush only takes place once the push-button is released.

Dual flush 3L/6L can be adjusted to 2L/4L.

Outlet connection for PVC tube Ø 26/32mm.

Acoustic level complies with European standard EN 12541 (class II acoustic level).

Base flow rate: 1 L/sec.

Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.

10-year warranty.

#### Kit contents:

(763BOX): recessed housing with cover, valve configured for system flush, vacuum breaker, stopcock, connection accessories.

(763040): control plate, collar for waterproofing, time flow cartridge.

#### **ADVANTAGES**



Soft-touch operation



Direct flush: no standing water



Dual flush 3L/6L



Waterproof housing, adjustable and modular

# **DELABIE**

# TECHNICAL CHARACTERISTICS

## TEMPOFLUX 3 direct flush WC valve - Ref.763BOX-763040

Technology	Time flow
Height	170 mm
Connector	F3⁄4"
Finish	Chrome-plated metal
Width	170 mm
Depth	93 - 190 mm



