DELABIE

# TEMPOFLUX 2 direct flush valve



Ref. 762902

Direct flush WC valve

## DESCRIPTION

**TEMPOFLUX 2 direct flush valve - Ref.762902**

Flush system without cistern: directly connected to pipework.
Chrome-plated metal wall plate Ø 195mm.
Multipurpose recessing housing.
Recessing depth can be adjusted from 0 - 20mm.
3L/6L dual flush, can be adjusted to 2L/4L.
Soft-touch operation.
Vacuum breaker.
Integrated stopcock and flow rate / flush volume adjuster.
Solid brass body.
Chrome-plated metal push-button.
In-line inlet M¾".
Outlet connection for PVC tube Ø 26/32mm.
Acoustic level complies with European standard EN 12541 class II.
Base flow rate: 1 L/sec.
Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.
10-year warranty.

This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).


## ADVANTAGES

- Soft-touch operation
- Dual flush 3L/6L
- No cistern: no stagnant water
- Recessed installation

## TECHNICAL CHARACTERISTICS

**TEMPOFLUX 2 direct flush valve - Ref.762902**

| | |
|---|---|
| Technology | Time flow |
| Flow rate | 3 l / 6 l |
| Connector | 3/4" |
| Finish | Chrome-plated metal |




© Delabie