

TEMPOMATIC 3 electronic tap

Ref. 44200615

Integrated batteries, Ø 15mm stopcock







DESCRIPTION

TEMPOMATIC 3 electronic tap - Ref.44200615

Deck-mounted electronic basin tap:
 Battery-operated with integrated 223 6V Lithium batteries.
 Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated solid brass body.
 Cap fixed in place by two concealed screws, with pictogram to easily identify sensor.
 PEX flexible Ø 15mm for compression fittings with stopcock and filter.
 Fixing reinforced by 2 stainless steel rods.
 Anti-blocking security.
 Suitable for people with reduced mobility.
 10-year warranty.

ADVANTAGES

-  Batteries integrated in mixer body
-  90% water savings
-  Total hygiene: no manual contact
-  Duty flush limits bacterial proliferation

TECHNICAL CHARACTERISTICS

TEMPOMATIC 3 electronic tap - Ref.44200615

Technology	Electronic
Flow rate	3 lpm
Connector	M1/2" Ø 15mm
Supply	6V battery
Supply	6V batteries
Drop Height	100 mm
Spout Length	120 mm
Installation:	Deck-mounted

