

BINOPTIC MIX electronic mixer

Ref. 378MCH15

Mains supply, Ø 15mm conical inlets

DESCRIPTION

BINOPTIC MIX electronic mixer - Ref.378MCH15

Deck-mounted electronic basin mixer:
 Independent IP65 electronic control unit.
 230/12V mains supply with transformer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
 Active, infrared movement detection, sensor at the end of the spout optimises detection.
 Chrome-plated solid brass body.
 PEX flexibles with filters, solenoid valves and Ø 15mm conical inlets.
 Fixing reinforced by 2 stainless steel rods.
 Anti-blocking security.
 Spout with a smooth interior and low volume of water (limits bacterial niches).
 Side temperature control with adjustable maximum temperature limiter.
 10-year warranty.





TECHNICAL CHARACTERISTICS

BINOPTIC MIX electronic mixer - Ref.378MCH15

Technology	Electronic
Flow rate	3 lpm
Supply	230/12V mains supply
Drop Height	110 mm
Spout Length	135 mm
Installation:	Deck-mounted



ADVANTAGES

-  90% water savings
-  Hygiene lever: no manual contact
-  Independent IP65 electronic control unit
-  Anti-bacterial proliferation duty flush

