

SECURITHERM BIOCLIP thermostatic basin mixer

Ref. H96051

Single hole, sequential thermostatic mixer H. 85mm L. 120mm



DESCRIPTION

SECURITHERM BIOCLIP thermostatic basin mixer - Ref.H96051

Deck-mounted thermostatic SECURITHERM basin mixer.

BIOCLIP: mixer is easy to remove for cleaning and disinfection.

Sequential thermostatic mixer: opens and closes with cold water.

Single hole mixer with straight spout H. 85mm L. 120mm fitted with a hygienic flow straightener with no impurity retention and thermal shock-resistant.

Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.

Securitouch thermal insulation prevents burns.

No cross flow between the cold and hot water.

No non-return valves on the inlets.

Scale-resistant sequential thermostatic cartridge for single control of flow rate and temperature.

Cold water temperature adjusts up to 40°C with temperature limiter set at 40°C.

Thermal and chemical shocks are possible.

Body and spout with smooth interiors and low water volume.

Flow rate regulated at 7 lpm.

No manual contact thanks to Hygiene control lever L. 146mm.

No pop-up waste.

Fixing reinforced by 2 stainless steel rods.

Ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

10-year warranty.

Also available with copper tails.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM BIOCLIP thermostatic basin mixer - [Ref.H96051](#)

Technology	SECURITHERM BIOCLIP sequential Securitouch
Flow rate	7 lpm
Connector	F3/8"
Finish	Chrome-plated brass
Drop Height	85 mm
Spout Length	120 mm
Temperature limiter	40 °C

