

SECURITHERM thermostatic basin mixer

Ref. H9600610L

Single hole sequential thermostatic mixer, H. 85mm L. 120mm



DESCRIPTION

SECURITHERM thermostatic basin mixer - [Ref.H9600610L](#)

Deck-mounted SECURITHERM thermostatic basin mixer.
Sequential thermostatic mixer: opens and closes with cold water.
Single hole mixer with straight spout H. 85mm L. 120mm fitted with a hygienic flow straightener, no build-up of impurities and withstands thermal shocks.
Anti-scalding failsafe: hot water shuts off automatically if cold water supply fails.
Securitouch thermal insulation prevents burns.
No risk of cross flow between hot and cold water.
No non-return valve on the inlets.
Scale-resistant thermostatic sequential cartridge for single control adjustment of flow rate and temperature.
Temperature can be adjusted from cold water up to 40°C with maximum temperature limiter set at 40°C.
Thermal and chemical shocks are possible.
Body and spout with smooth interiors and low water volume.
Flow rate regulated at 7 lpm.
No manual contact thanks to Hygiene control lever L. 100mm.
Without pop-up waste.
Supplied with copper tails and stopcocks in chrome-plated brass Ø 15mm.
Reinforced fixing via 2 stainless steel rods.
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
10-year warranty.
Also available with PEX flexibles.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic basin mixer - [Ref.H9600610L](#)

Technology	Single control SECURITHERM, Securitouch
Height	178 mm
Flow rate	7 lpm
Connector	M1/2" Ø 15mm
Finish	Chrome-plated brass
Drop Height	85 mm
Spout Length	120 mm
Temperature limiter	40 °C

