

## TEMPOSTOP time flow tap 2 controls

Ref. 748210

Anti-blocking version (AB)



### DESCRIPTION

#### TEMPOSTOP time flow tap 2 controls - Ref.748210

Time flow basin tap for cross wall installation:

Time flow ~7 seconds.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm.

2 controls: 1 button for mixed water and 1 button for cold water.

Tamperproof scale-resistant flow straightener.

Chrome-plated solid brass body M $\frac{1}{2}$ ".

Control ? 200mm, spout ? 230mm.

Ligature-resistant button is flush to wall.

Anti-rotating pin and back nut.

AB anti-blocking system: water will flow only when the push-button is released.

10-year warranty.

### ADVANTAGES



Cross wall installation



Anti-blocking system



85% water savings



Maintenance outside area of use

### TECHNICAL CHARACTERISTICS

#### TEMPOSTOP time flow tap 2 controls - Ref.748210

|              |                   |
|--------------|-------------------|
| Technology   | Time flow         |
| Length       | 200 mm            |
| Flow rate    | 3 lpm             |
| Connector    | M $\frac{1}{2}$ " |
| Spout Length | 75 mm             |