DELABIE

SECURITHERM shower mixer

Ref. 792BOX-792452

Thermostatic electronic



DESCRIPTION

SECURITHERM shower mixer - Ref.792BOX-792452

Recessed thermostatic electronic shower mixer:
Tamperproof polished satin stainless steel plate 195 x 220mm.
Waterproof recessing housing.
16 to 30mm allowance for different wall finishes.
SECURITHERM thermostatic mixer 3/4".
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Adjustable temperature from 32° to 40°C, pre-set at 38°C.
Battery-operated with 223 6V Lithium battery.
Infrared presence detection. Shower starts when hand is 4cm from the sensor.
Shuts off voluntarily or automatically after ~60 seconds.
Duty flush (~60 seconds every 24 hours after the last use).
Flow rate 9 lpm at 3 bar.
Concealed fixings, M½" stopcocks.
Integrated non-return valves and filters.
Chrome-plated Bayblend® control knob.
Suitable for people with reduced mobility.
10-year warranty.

(792BOX): recessed housing with protective cover, valve configured for system flush, stop cocks, installation and connection accessories.
(792452): control plate, valve, thermostatic cartridge, solenoid valve, filters and non-return valves, collar with waterproof seal, ROUND shower head.

ADVANTAGES

- Total hygiene: operate without manual contact
- Anti-bacterial duty flush
- Thermostatic control
- Instant shut-off if cold water supply fails


© Delabie

DELABIE

TECHNICAL CHARACTERISTICS

SECURITHERM shower mixer - Ref.792BOX-792452

Technology	Electronic
Height	195 mm
Flow rate	9 lpm
Connector	1/2"
Supply	6V battery
Width	220 mm
Water supply	Concealed



© Delabie