DELABIE

SECURITHERM shower kit



Ref. 792BOX-792219

Thermostatic time flow



DESCRIPTION

SECURITHERM shower kit - Ref.792BOX-792219

Recessed thermostatic time flow shower kit:
Tamperproof satin finish stainless steel plate 195 x 220mm.
Waterproof recessing housing.
16 - 30mm allowance for different wall finishes.
SECURITHERM thermostatic mixer ¾".
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Temperature can be adjusted from 32° - 40°C, pre-set at 38°C.
Soft-touch operation.
Time flow, ~30 seconds.
Flow rate set at 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
Concealed fixings, M½" stopcocks.
Integrated filters and non-return valves.
Chrome-plated Bayblend® control button.
Suitable for people with reduced mobility.
10-year warranty.

Kit contents:
(792BOX): recessed housing with cover, valve configured for system flush, stopcocks and connection accessories.
(792219): control plate, valve, thermostatic cartridge, time flow cartridge, collar for waterproofing, shower head.

ADVANTAGES


- Thermostatic temperature regulation
- Instant shut-off if cold water fails
- 80% water savings


© Delabie


TECHNICAL CHARACTERISTICS

SECURITHERM shower kit - Ref.792BOX-792219

Technology	Time flow
Height	195 mm
Flow rate	6 lpm
Connector	1/2"
Width	220 mm
Water supply	Concealed







© Delabie