DELABIE

TEMPOMIX shower kit



Ref. 790909

Single control time flow



DESCRIPTION

TEMPOMIX shower kit - Ref.790909

Recessed time flow shower kit:
Chrome-plated wall plate Ø 195mm.
Standard recessing housing.
Recessing depth can be adjusted from 28 to 43mm.
TEMPOMIX 3/4" single control mixer.
Ligature-resistant collar.
Temperature control and operation via the push-button.
Maximum temperature limiter (can be adjusted by the installer).
Time flow ~30 seconds.
Flow rate 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
M1/2" connectors for copper tubes Ø 14mm.
Integrated non-return valves and filters.
Chrome-plated metal push-button.
Suitable for people with reduced mobility.
10-year warranty.
Integrated non-return valves and filters. This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).


ADVANTAGES


- 80% water savings
- Time flow system tested to over 500000 operations
- Wall recessed installation
- Soft-touch operation

TECHNICAL CHARACTERISTICS

TEMPOMIX shower kit - Ref.790909

Technology	Time flow
Flow rate	6 lpm
Connector	1/2"





© Delabie