DELABIE

TEMPOMIX shower mixer

Ref. 790427

Single control time flow



DESCRIPTION

TEMPOMIX shower mixer - Ref.790427

Recessed time flow shower kit:
Stainless steel wall plate 160 x 160mm.
Standard recessing housing.
Recessing depth can be adjusted from 28 to 48mm.
TEMPOMIX ¾" single control mixer.
Ligature-resistant collar.
Temperature control and operation via the push-button.
Maximum temperature limiter (can be adjusted by the installer).
Time flow ~30 seconds.
Flow rate 12 lpm at 3 bar.
M½" connections for Ø 14mm copper tubes.
Integrated non-return valves and filters.
Chrome-plated metal push-button.
Integrated non-return valves and filters.
10-year warranty.

This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).


ADVANTAGES

- Wall recessed installation
- Time flow system tested to over 500000 operations
- Waterproof recessing housing
- Soft-touch operation

TECHNICAL CHARACTERISTICS

TEMPOMIX shower mixer - Ref.790427

Technology	Time flow
Height	160 mm
Flow rate	12 lpm
Connector	1/2"
Width	160 mm



© Delabie