

TEMPOMIX shower mixer

Ref. 790427

Single control time flow



DESCRIPTION

TEMPOMIX shower mixer - Ref.790427

Recessed time flow shower kit:
 Stainless steel wall plate 160 x 160mm.
 Standard recessing housing.
 Recessing depth can be adjusted from 28 to 48mm.
 TEMPOMIX 3/4" single control mixer.
 Ligature-resistant collar.
 Temperature control and operation via the push-button.
 Maximum temperature limiter (can be adjusted by the installer).
 Time flow ~30 seconds.
 Flow rate 12 lpm at 3 bar.
 1/2" connections for Ø 14mm copper tubes.
 Integrated non-return valves and filters.
 Chrome-plated metal push-button.
 Integrated non-return valves and filters.
 10-year warranty.





This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

TECHNICAL CHARACTERISTICS

TEMPOMIX shower mixer - Ref.790427

Technology	Time flow
Height	160 mm
Flow rate	12 lpm
Connector	1/2"
Width	160 mm

ADVANTAGES

-  Wall recessed installation
-  Time flow system tested to over 500000 operations
-  Waterproof recessing housing
-  Soft-touch operation

