

SECURITHERM shower panel

Ref. 792310UK

Thermostatic time flow

DESCRIPTION

SECURITHERM shower panel - Ref.792310UK

Thermostatic time flow shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
With concealed inlet via flexibles.
SECURITHERM thermostatic mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
Soft-touch operation.
Time flow ~30 seconds.
Flow rate 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head and automatic flow rate regulation.
Concealed fixings.
Filters and non-return valves.
Suitable for people with reduced mobility.
10-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref.792310UK

Technology	Time flow
Height	1050 mm
Flow rate	6 lpm
Connector	M1/2"
Finish	Aluminium
Temperature limiter	Thermostatic
Width	210 mm
Depth	65 mm
Water supply	Concealed



ADVANTAGES



Thermostatic temperature regulation



Instant shut-off if cold water fails



80% water savings



Aluminium panel, brass controls

