

SECURITHERM shower panel

Ref. 792313CF

Time flow thermostatic, comfort 10 lpm

DESCRIPTION

SECURITHERM shower panel - Ref.792313CF

Thermostatic time flow shower panel:
Large model stainless steel shower panel for wall mounted, exposed installation.
Concealed inlet via flexibles M1/2".
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
Thermal shocks are possible.
Soft-touch operation.
Time flow ~30 seconds.
Flow rate 10 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
M1/2" stopcocks.
Concealed fixings.
Filters and non-return valves.
10-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref.792313CF

Technology	Time flow
Height	1220 mm
Flow rate	10 lpm
Connector	M1/2"
Finish	Stainless steel
Temperature limiter	Thermostatic
Width	250 mm
Depth	100 mm
Water supply	Concealed



ADVANTAGES



Thermostatic temperature regulation



Immediate shut-off if cold water fails



Stainless steel sheath, brass controls



80% water savings

