

## TEMPOMATIC 4 urinal valve

Ref. 430P006

Electronic with integrated batteries



### DESCRIPTION

#### TEMPOMATIC 4 urinal valve - Ref.430P006

Recessed electronic urinal valve:

123 6V Lithium battery-operated.

Satin finish stainless steel wall plate 145 x 145mm with integrated electronics.

Recessing housing:

- Hydraulic connection to the outside.
- Adjusts to all types of installation (rails, solid walls, panels).
- Compatible with wall finishes 10 - 120mm (while maintaining the minimum recessing depth of 105mm).
- Integrated solenoid valve is accessible from the front.
- TEMPOMATIC 4 urinal valve F½" is compatible with sea water and grey water.

Detection delay is 10 seconds.

3 programmes (rinsing volume can be set according to urinal type).

High-frequency mode (exclusive to DELABIE):

- Short rinse after each user.
- Additional rinse at the end of the busy period.

Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after the last use: prevents vacuums.

Flow rate pre-set at 0.3 L/sec. at 3 bar.

Suitable for people with reduced mobility.

10-year warranty.

### TECHNICAL CHARACTERISTICS

#### TEMPOMATIC 4 urinal valve - Ref.430P006

|            |                              |
|------------|------------------------------|
| Technology | Electronic                   |
| Inaltime   | 150 mm                       |
| Debit      | 0.3 l/sec                    |
| Finisaj    | Satin finish stainless steel |
| Supply     | 6V battery                   |
| Width      | 175 mm                       |
| Depth      | 105 - 205 mm                 |

### ADVANTAGES



Total hygiene: no manual contact



3 rinsing programmes and high-frequency mode



Duty flush prevents proliferation of bacteria

