

## SECURITHERM EP BIOSAFE pressure- balancing basin mixer

Ref. 26216EP

Single hole mechanical mixer with no spout H. 95mm L. 110mm

### DESCRIPTION

#### SECURITHERM EP BIOSAFE pressure-balancing basin mixer -

##### Ref.26216EP

Deck-mounted mechanical basin mixer with pressure-balancing. Single hole mechanical mixer H. 95mm L. 110mm. No spout: BIOSAFE hygienic outlet integrated into the body. Ø 35mm ceramic cartridge with pre-set maximum temperature limiter. Anti-scalding safety: HW flow rate is reduced if CW supply fails. Stable temperature regardless of pressure and flow rate variations in the system. Securitouch thermal insulation prevents burns. Thermal shocks are possible without removing the control lever or shutting off the cold water supply. Mixer body with smooth interior and very low water volume (reduces bacterial development). Flow rate limited to 4 lpm at 3 bar. Solid control lever. Ergonomic pop-up waste 1 1/4" in brass. Mixer with copper tails and Ø 15mm stopcocks. Filters and non-return valves. Fixing reinforced by two stainless steel rods. Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, retirement and care homes, hospitals and clinics. Single hole mixer suitable for people with reduced mobility. Mixer with 10-year warranty. Also available with PEX flexibles.



### ADVANTAGES

## TECHNICAL CHARACTERISTICS

### SECURITHERM EP BIOSAFE pressure-balancing basin mixer -

#### Ref.26216EP

Technology	SECURITHERM EP BIOSAFE
Inaltime	180 mm
Lungime	220 mm
Debit	4 lpm la 3 bari
Conector	1/2"
Finisaj	Chrome-plated brass
Drop Height	95 mm
Spout Length	110 mm
Temperature limiter	Yes

