

## TEMPOFLUX time flow urinal valve

Ref. 778755

Time flow 3 seconds. For standard urinals Ø 35mm.  
Straight neck tube







### DESCRIPTION

#### TEMPOFLUX time flow urinal valve - Ref.778755

Exposed time flow urinal valve:  
For standard or siphon action urinals.  
For wall-mounted exposed installation.  
Soft-touch operation.  
Time flow pre-set at 3 seconds.  
Vacuum breaker.  
Flow rate pre-set at 0.15 l/sec. at 3 bar, can be adjusted up to 0.3 l/sec.  
Innovative stopcock and flow rate adjustment system integrated in the wall plate (patented).  
Complies with European standard EN 12541 (acoustic level class II).  
Chrome-plated solid brass body M $\frac{1}{2}$ ".  
With a chrome-plated neck tube and connection washer Ø 35mm.  
Angled for recessed inlet .  
Suitable for people with reduced mobility.  
10-year warranty.

### ADVANTAGES

-  ECO time flow 3 seconds
-  Soft-touch operation
-  Stopcock built-in to wall plate
-  Smooth design

### TECHNICAL CHARACTERISTICS

#### TEMPOFLUX time flow urinal valve - Ref.778755

Technology	Time flow
Inaltime	320 mm
Debit	0.15 l/sec.
Conector	1/2"

