

## TEMPOFLUX time flow urinal valve

Ref. 778765

Time flow 7 seconds. For standard urinal Ø 35mm. In-line tube

### DESCRIPTION

#### TEMPOFLUX time flow urinal valve - Ref.778765

Exposed time flow urinal valve:  
For standard or siphon action urinals.  
Wall-mounted exposed installation.  
Soft-touch operation.  
Time flow pre-set at ~7 seconds.  
Vacuum breaker.  
Flow rate pre-set at 0.15 L/sec. at 3 bar, can be adjusted up to 0.3 L/sec.  
Innovative stopcock and flow rate adjustment system integrated in the wall plate (patented).  
Complies with European standard EN 12541 (class II acoustic level).  
Chrome-plated solid brass body M $\frac{1}{2}$ ".  
30mm in-line chrome-plated tube and connection washer Ø 35mm.  
Angled for recessed inlet.  
Suitable for people with reduced mobility.  
10-year warranty.





### TECHNICAL CHARACTERISTICS

#### TEMPOFLUX time flow urinal valve - Ref.778765

Technology	Time flow
Inaltime	320 mm
Debit	0.15 l/sec
Conector	1/2"
Width to the wall	50 mm



### ADVANTAGES

-  Time flow 7 seconds
-  Soft-touch operation
-  Stopcock built-in to wall plate
-  Sleek design

