

TEMPOMATIC MIX 4 electronic mixer

Ref. 490100LH

Recessed mains supply

DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref.490100LH

Deck-mounted electronic basin mixer:
230/6V recessed mains supply.
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated metal body.
Cap fixed in place by 2 concealed screws.
PEX flexibles F3/8" with filters and non-return valves.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Side temperature control with long lever and adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
10-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref.490100LH

Technology	Electronic
Debit	3 lpm
Conector	F3/8"
Supply	230/6V mains supply (recessed)
Drop Height	75 mm
Spout Length	110 mm
Installation:	Deck-mounted



ADVANTAGES



Total hygiene: no manual contact



90% water savings



Recessed mains supply



Anti-bacterial proliferation duty flush

