

## Anti-bacterial BIOFIL cartridge filter

Ref. 30051A.10P

Single use cartridge A, laminar flow



### DESCRIPTION

#### Anti-bacterial BIOFIL cartridge filter - Ref.30051A.10P

Single use anti-bacterial BIOFIL cartridge A with sterilising grade of 0.1µm absolute-rated.

Cartridge filter without waterproof seal and with laminar effect spray.

Hydrophilic polyethylene hollow fibres.

Filtration area: 1,400cm<sup>2</sup>.

Filtration flow rate: 12 lpm at 3 bar (filter only, excludes any flow rate restrictor/regulator in the shower).

Maximum upstream pressure at point-of-use: 5 bar.

Length of maximum use: 62 days after installation.

Compatible with and resistant to chemical and thermal shocks.

CE class 1 non-sterile anti-bacterial filters.

Weight: 80g.

Packed in boxes of 10 pieces, individually wrapped, non-sterile.

### ADVANTAGES

### TECHNICAL CHARACTERISTICS

#### Anti-bacterial BIOFIL cartridge filter - Ref.30051A.10P

| Technology | Terminal de filtrare |
|------------|----------------------|
| Inaltime   | 75 mm                |
| Lungime    | Ø 58 mm              |
| Debit      | 12 lpm               |

