

TEMPOMATIC 4 electronic tap

Ref. 440006

Integrated batteries, stopcock

DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref.440006

Deck-mounted electronic basin tap:
Battery-operated with integrated 123 6V Lithium batteries.
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated metal body.
Cap fixed in place by 2 concealed screws.
PEX flexible with stopcock F3/8" and filter.
Fixing reinforced by two stainless steel rods.
Anti-blocking security.
Suitable for people with reduced mobility.
10-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref.440006

Technology	Electronic
Debit	3 lpm
Conector	F3/8"
Supply	6V batteries
Drop Height	75 mm
Spout Length	110 mm
Installation:	Deck-mounted



ADVANTAGES



Total hygiene: no manual contact



90% water savings



Batteries integrated into the body of the tap



Anti-bacterial proliferation duty flush

