

TEMPOMATIC MIX electronic mixer with removable BIOCLIP spout

Ref. 20870T1

Tall single hole infrared mixer with stainless steel
swivelling spout



DESCRIPTION

TEMPOMATIC MIX electronic mixer with removable BIOCLIP spout -

Ref.20870T1

Deck-mounted electronic basin mixer.
Electronic mixer with high, removable, swivelling BIOCLIP spout H. 160mm.
Single hole mixer supplied with 2 removable stainless steel spouts
L.185mm Ø 28mm.
Independent IP65 electronic control unit.
Mains supply via 230/12V transformer.
Body and spout with smooth interiors (reduces niches where bacteria can develop).
Adjustable duty flush (pre-set to approx. 60 secs every 24h after last use) to prevent water stagnation in the network in the event of prolonged periods of non-use.
Flow rate limited to 5 lpm at 3 bar.
Shockproof infrared presence detection sensor.
Chrome-plated solid brass body with reinforced fixing via 2 stainless steel rods.
Hygiene lever L. 100mm controls temperature.
PEX flexibles with filters and M3/8" solenoid valve.
Anti-blocking safety.
Solenoid valves upstream of the mixing chamber.
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Suitable for people with reduced mobility.
Mixer with 10-year warranty.

Two shut-off options:

- standard mode: timed flow with automatic shut-off.
- ON/OFF mode: user shuts off flow voluntarily after 30 minutes.

Thermal shocks are possible.

Position the sensor to the side of the mixer in the On/Off mode.

ADVANTAGES

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX electronic mixer with removable BIOCLIP spout -

Ref.20870T1

Technology	Electronic mixer
Inaltime	280 mm
Debit	5 lpm
Conector	M3/8"
Finisaj	Chrome-plated brass
Drop Height	160 mm
Spout Length	185 mm

