Grab bar with left support stainless steel brushed

Ref. GW11 10 04 01

AISI 304 stainless steel, satin



DESCRIPTION

Grab bar with left support stainless steel brushed - Ref.GW11 10 04 01

No built- in angle bar with three points of support located on the endings.
The bar consists of an AISI 304 stainless steel tube with 32 mm of diameter and 1.5 mm of thickness.
The tube is bended on ÒUÓ shape for main part and ÒLÓ shape on the left.
The three mounting flanges are made of zinc-plated stainless steel plate with anticorrosion treatment of 2.5 mm of thickness and 77,5 mm of diameter. Mounting flanges have
three holes for wall attachment and snap flange covers with 0.5 mm of thickness.
The brushed stainless steel assembled unit has suitable resistance to corrosion.
The bar is fixed to the wall by means of 9 nylon wall plugs (8X50) and AISI304 stainless steel screws (5X60).
Grab bar will support loads in excess of 120Kg if properly installed

ADVANTAGES

- Anti-fingerprint treatment
- Easily removable head

TECHNICAL CHARACTERISTICS

Grab bar with left support stainless steel brushed - Ref.GW11 10 04 01

Lungime	600mm
Finisaj	AISI 304 stainless steel, satin
Width	190mm
Grosime	1.5mm
Diameter	32mm

© Genwec