3 sides grab bar stainless steel polished left

Ref. GW11 20 04 02

AISI 304 stainless steel, polished



DESCRIPTION

3 sides grab bar stainless steel polished left - Ref.GW11 20 04 02

3-sided angled bar with 4 points of support.
The tube has an outside diameter of 32 mm with a thickness of 1,5 mm.
The mounting flanges are made of zinc-plated stainless steel plate with anticorrosion treatment of 2.5 mm of thickness and 75 mm of diameter.
The endings of the tube and the mounting flanges are threading M10.
Mounting flanges have three holes for wall attachment and snap flange covers with 0.5 mm of
thickness.
The assembled unit has suitable resistance to corrosion.
The grab bar is fixed to the wall by means of nylon wall plugs 8X50 and AISI 304 stainless steel screws 5X60.
Grab bar will support loads in excess of 120Kg if properly installed.
The total measures of the product are 760 x 460 x 610 mm.

ADVANTAGES

- Anti-fingerprint treatment
- Easily removable head

TECHNICAL CHARACTERISTICS

3 sides grab bar stainless steel polished left - Ref.GW11 20 04 02

Inaltime	760mm
Finisaj	AISI 304 stainless steel, polished
Width	460mm 610mm
Grosime	1.5mm
Diameter	32mm

© Genwec