Angled grab bar 300x300mm white steel

Ref. GW11 22 03 00

White epoxy



DESCRIPTION

Angled grab bar 300x300mm white steel - Ref.GW11 22 03 00

135¼ Angled bar with two points of support located on the endings.
The bar consists of an white opoxy tube with 32 mm of diameter and 1.5 mm of thickness bended 90¼ on the endings.
The two mounting flanges are made of zinc-plated stainless steel plate with anticorrosion treatment of 2.5 mm of thickness and 75 mm of diameter.
The endings of the tube and the mounting flanges are threading.
Mounting flanges have three holes for wall attachment and snap flange covers with 0.5 mm of thickness.
The brushed stainless steel assembled unit has suitable resistance to corrosion.
The bar is fixed to the wall and the floor by means of 6 nylon wall plugs 8X50mm and AISI 304 stainless steel screws 5X60.
Grab bar will support loads in excess of 120Kg if properly installed

ADVANTAGES

- Anti-fingerprint treatment
- Easily removable head

TECHNICAL CHARACTERISTICS

Angled grab bar 300x300mm white steel - Ref.GW11 22 03 00

Lungime	300mm
Finisaj	White epoxy
Width	300mm
Grosime	1.5mm
Diameter	32mm

© Genwec