

TEMPOMATIC 4 electronic tap

Ref. 44000015

Recessed mains supply, 15mm stopcock

DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref.44000015

Deck-mounted electronic basin tap:
230/6V recessed mains supply.
Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 sec. every 24h after last use).
Active, infrared presence detection, sensor at the end of the spout optimises detection.
Chrome-plated solid brass body.
Cap fixed in place by two concealed screws.
PEX flexible with stopcock, filter and Ø 15mm conical inlet.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
10-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref.44000015

Technology	Electronic
Debit	3 lpm
Conector	M1/2" Ø 15mm
Supply	230/6V mains supply (recessed)
Supply	230/6V (recessed mains supply)
Drop Height	75 mm
Spout Length	110 mm
Installation:	Deck-mounted



ADVANTAGES



Total hygiene: no manual contact



90% water savings



Recessed mains supply



Duty flush limits bacterial proliferation

