


BINOPTIC electronic tap

Ref. 379D1315

Mains supply, Ø 15mm conical inlets



DESCRIPTION

BINOPTIC electronic tap - Ref.379D1315

Recessed electronic basin tap:
Independent IP65 electronic control unit.
230/12V mains supply with transformer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm.
Scale-resistant flow straightener.
Duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Active, infrared movement detection, sensor at the end of the spout optimises detection.
Filter, solenoid valve and Ø 15mm conical inlet.
Chrome-plated solid brass body.
Chrome-plated spout L. 200mm for recessed installation.
Anti-blocking security.
Spout with a smooth interior and low water volume (limits bacterial niches).
10-year warranty.

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Independent IP65 electronic control unit



Anti-bacterial proliferation duty flush

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref.379D1315

Technology	Electronic
Debit	3 lpm
Conector	M1/2" Ø 15mm
Supply	230/12V mains supply
Spout Length	135 mm
Installation:	Cross wall

