

SECURITHERM BIOCLIP thermostatic sink mixer

Ref. H9610S

Wall-mounted thermostatic sequential mixer



DESCRIPTION

SECURITHERM BIOCLIP thermostatic sink mixer - Ref.H9610S

Wall-mounted thermostatic sink mixer with BIOCLIP removable spout.
Mixer supplied with 1 removable disposable spout.
Thermostatic sequential mixer: opens and closes with cold water.
Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.
Securitouch thermal insulation prevents burns.
No risk of cross flow between hot and cold water.
No non-return valves on the inlets.
Scale-resistant thermostatic sequential cartridge for sequential control of flow rate and temperature.
Temperature can be adjusted from cold water up to 40°C with maximum temperature limiter set at 40°C.
Thermal and chemical shocks are possible.
Body and spout with smooth interiors and low water volume.
Flow rate regulated at 7 lpm at 3 bar.
Chrome-plated brass body.
No manual contact thanks to Hygiene control lever L. 146mm.
Mixer with 150mm centres supplied with offset standard connectors M1/2" M3/4" suitable for hospitals.
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Suitable for people with reduced mobility.
10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM BIOCLIP thermostatic sink mixer - Ref.H9610S

Technology	SECURITHERM BIOCLIP sequential, Securitouch
Inaltime	141 mm
Debit	7 lpm
Conector	M1/2"
Finisaj	Chrome-plated brass
Spout Length	185 mm
Temperature limiter	40 °C
Width	184 mm

