

Sequential mechanical basin mixer

Ref. 2640

Sequential mechanical mixer with swivel/fixed spout



DESCRIPTION

Sequential mechanical basin mixer - [Ref.2640](#)

Wall-mounted sequential mechanical basin mixer.
Opens and closes with cold water, with 70° lever turning range.
Flat, swivelling under spout L. 120mm with hygienic BIOSAFE outlet.
Spout can be easily fixed in place.
Securitouch thermal insulation prevents burns.
Mixer with Ø 35mm ceramic cartridge.
Pre-set maximum temperature limiter.
Body and spout with narrow tubes with smooth interiors and very low water volume reduces bacterial development.
The speed of the water in the tubes reduces biofilm development considerably.
Thermal shocks are possible without removing the control lever or shutting off the cold water supply.
Flow rate regulated at 5 lpm.
Chrome-plated brass body.
Hygiene control lever L. 200mm requires no manual contact.
Supplied with offset STOP/CHECK wall connectors M1/2" M3/4" ideal for the issues faced by hospitals.
Recommended installation height: 110 - 200mm above the basin surface.
Sequential mechanical mixer ideal for Healthcare facilities, retirement and care homes, hospitals and clinics.
Suitable for people with reduced mobility.
10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

Sequential mechanical basin mixer - Ref.2640

Technology	Securitouch
Debit	5 lpm
Conector	M1/2"
Finisaj	Chrome-plated brass
Spout Length	120 mm

