

Sequential mechanical basin mixer

Ref. 2640S

Sequential mechanical mixer with swivelling/fixed spout
L. 120mm



DESCRIPTION

Sequential mechanical basin mixer - Ref.2640S

Wall-mounted sequential mechanical mixer.
Opens and closes with cold water, with 70° lever turning range.
Flat, swivelling under spout L. 120mm with hygienic BIOSAFE outlet.
Spout can be easily fixed in place.
Securitouch thermal insulation prevents burns.
Mixer with Ø 35mm ceramic cartridge.
Pre-set maximum temperature limiter.
Body and spout with narrow tubes with smooth interiors and very low water volume.
The speed of the water in these narrow tubes reduces biofilm development considerably.
Thermal shocks are possible without removing the control lever or shutting off the cold water supply.
Flow rate regulated at 5 lpm.
Chrome-plated brass body.
Hygiene control lever L. 200mm requires no manual contact.
Supplied with offset standard wall connectors M1/2" M3/4".
Recommended installation height: 110 - 200mm above the basin surface.
Sequential mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Suitable for people with reduced mobility.
10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

Sequential mechanical basin mixer - Ref.2640S

| | |
|--------------|---------------------|
| Technology | Securitouch |
| Debit | 5 lpm |
| Conector | M1/2" |
| Finisaj | Chrome-plated brass |
| Spout Length | 120 mm |

