

SECURITHERM EP pressure-balancing basin mixer

Ref. 2446EP

Wall-mounted mixer with swivelling spout L. 150mm,
sculptured lever



DESCRIPTION

SECURITHERM EP pressure-balancing basin mixer - Ref.2446EP

Wall-mounted SECURITHERM Pressure Balancing (EP) basin mixer.
Anti-scalding safety: HW flow is reduced if CW supply fails (and vice versa).
Securitouch thermal insulation prevents burns.
Flat, swivelling under spout L. 150mm with hygienic flow straightener
suitable for fitting a BIOFIL terminal filter.
Ø 40mm pressure-balancing ceramic cartridge and pre-set maximum
temperature limiter.
Body and spout with smooth interiors and low water volume (reduces
niches where bacteria can develop).
Flow rate regulated at 5 lpm.
Body and spout with smooth interior and low water volume (reduces
bacterial development).
Chrome-plated brass body.
Sculptured control lever.
Supplied with STOP/CHECK connectors M1/2" M3/4" ideal for use in
hospitals.
10-year warranty.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref.2446EP

Technology	SECURITHERM EP, Securitouch
Debit	5 lpm
Conector	M1/2"
Finisaj	Chrome-plated brass
Spout Length	150 mm
Temperature limiter	41 °C

