

SECURITHERM sequential thermostatic basin mixer

Ref. H9601

Single hole sequential thermostatic mixer H. 95mm L. 120mm

DESCRIPTION

SECURITHERM sequential thermostatic basin mixer - Ref.H9601

Deck-mounted SECURITHERM thermostatic basin mixer.

Thermostatic sequential mixer: opens and closes with cold water.

No risk of cross flow between the hot and cold water.

No non-return valves on the inlets.

Single hole mixer with curved spout H. 95mm L. 120mm fitted with a hygienic flow straightener for no impurity retention and thermal shock-resistant.

Anti-scalding failsafe: immediate shut-off if cold or hot water supply fails.

Securitouch thermal insulation prevents burns.

Scale-resistant sequential thermostatic cartridge for single lever control of flow rate and temperature.

Temperature can be adjusted from cold water up to 40°C with temperature limiter set at 40°C.

Thermal or chemical shocks are possible.

Body and spout with smooth interiors and low water volume.

Flow rate regulated at 5 lpm.

No manual contact thanks to Hygiene control lever L. 146mm.

Ergonomic brass pop-up waste 1 1/4".

Supplied with stainless steel F3/8" PEX flexibles with chrome-plated brass stopcocks.

Reinforced fixing via 2 stainless steel rods.

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Suitable for people with reduced mobility.

10-year warranty.

Also available with copper tails.



ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM sequential thermostatic basin mixer - Ref.H9601

Technology	Mixer sequential thermostatic
Debit	5 lpm la 3 bari
Finisaj	Chrome-plated brass
Supply	3/8"
Drop Height	95 mm
Spout Length	120 mm
Temperature limiter	Yes

