

SECURITHERM thermostatic basin mixer

Ref. H96001

Single control thermostatic sequential mixer H. 85mm L. 120mm



DESCRIPTION

SECURITHERM thermostatic basin mixer - Ref.H96001

Deck-mounted SECURITHERM thermostatic basin mixer.

Thermostatic sequential mixer: opens and closes with cold water.

Single hole mixer with straight spout H. 85mm L. 120mm and fitted with a hygienic flow straightener with no water retention and able to withstand thermal shocks.

Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.

Securitouch thermal insulation prevents burns.

No risk of cross flow between hot and cold water.

No non-return valves on the inlets.

Scale-resistant sequential thermostatic cartridge for single lever control of flow rate and temperature.

Temperature control from cold water up to 40°C with maximum temperature limiter set at 40°C.

Thermal or chemical shocks are possible.

Body and spout with smooth interiors and low water volume.

Flow rate regulated at 7 lpm.

No manual contact thanks to Hygiene control lever L. 146mm.

No pop-up waste.

F3/8" PEX flexibles.

Reinforced fixing via 2 stainless steel rods.

Mixer ideal for healthcare facilities, nursing homes, hospitals and clinics.

Suitable for people with reduced mobility.

10-year warranty.

Also available with copper tails.

ADVANTAGES

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic basin mixer - [Ref.H96001](#)

Technology	SECURITHERM sequential Securitouch
Debit	7 lpm
Conector	F3/8"
Finisaj	Chrome-plated brass
Drop Height	85 mm
Spout Length	120 mm
Temperature limiter	40 °C

