

SECURITHERM thermostatic basin mixer

Ref. H9726

Single hole, dual control, thermostatic control mixer H. 205 L. 150

DESCRIPTION

SECURITHERM thermostatic basin mixer - Ref.H9726

SECURITHERM thermostatic dual control basin mixer.
Tall, single hole mixer with swivelling spout H. 205mm L. 150mm.
Anti-scalding failsafe: immediate shut-off if cold or hot water supply fails.
Spout with smooth interior and with BIOSAFE hygienic outlet, suitable for fitting a BIOFIL filter.
Scale-resistant thermostatic cartridge for temperature control.
¼-turn ceramic head for adjusting the flow rate.
Temperature can be adjusted, with two temperature limiters: first temperature limiter set at to 38°C (can be overridden), and second temperature limiter set at 41°C.
Thermal shocks are easy to undertake without removing the control knob or shutting off the cold water supply.
Flow rate regulated at 5 lpm.
ERGO control knobs.
Ergonomic pop-up waste, 1 1/4" in brass.
PEX flexibles F3/8" with filters and non-return valves.
Reinforced fixing via 2 stainless steel rods.
Ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Suitable for people with reduced mobility.
10-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic basin mixer - Ref.H9726

Technology	SECURITHERM thermostatic
Inaltime	307 mm
Lungime	205 mm
Debit	5 lpm
Conector	F3/8"
Finisaj	Chrome-plated brass
Spout Length	150 mm
Temperature limiter	41 °C



ADVANTAGES

