

Electronic sink mixer with BIOCLIP removable spout

Ref. 20871T1

Single hole infrared mixer, disposable, swivelling spout
H.160 L.180



DESCRIPTION

Electronic sink mixer with BIOCLIP removable spout - Ref.20871T1

Deck-mounted electronic mixer.

Electronic mixer with high, swivelling, removable BIOCLIP spout H. 160mm.
Single hole mixer supplied with 1 disposable, recyclable Hostaform® spout
L. 180mm Ø 22mm.

Independent IP65 electronic control unit.

Mains supply with 230/12V transformer.

Body and spout with smooth interiors (reduce niches where bacteria can develop).

Adjustable duty flush (pre-set flush for approximately 60 seconds every 24 hours after the last use) to prevent stagnation in the water supply if the system is not used for prolonged periods.

Flow rate limited to 5 lpm at 3 bar.

Shock-resistant infrared presence detection sensor.

Chrome-plated brass body with reinforced fixing via 2 stainless steel rods.

Hygiene lever L. 100mm controls temperature.

PEX flexibles with and M3/8" solenoid valves.

Anti-blocking security.

Solenoid valves upstream of the mixing chamber.

Mixer ideal for healthcare facilities, retirement homes, hospitals and clinics.

Suitable for people with reduced mobility.

Mixer with 10-year warranty.

Two shut-off options:

- standard mode - timed flow with automatic shut-off;
- ON/OFF mode - user shuts off flow voluntarily or automatic shut-off after 30 minutes.

Thermal shocks are possible.

Position the sensor on the side of the mixer in ON/OFF mode.

ADVANTAGES

TECHNICAL CHARACTERISTICS

Electronic sink mixer with BIOCLIP removable spout - [Ref.20871T1](#)

Technology	Electronic
Inaltime	280 mm
Debit	5 lpm
Conector	M3/8"
Finisaj	Chrome-plated brass
Drop Height	160 mm
Spout Length	180 mm

